

Teltek C80

Checkweigher

Dynamic weighing system



USER MANAGEMENT

The Teltek C80 Checkweigher is designed for robust applications using intuitive software based on Windows™ platform. The C80 inline checkweigher features a large 15" LED touch screen display for ease of use and maximum operator flexibility.

BENEFITS

Top of the line checkweigher that fulfil every need. Extremely well adapted for integration in all kind of data enviroment. This checkweigher comes in the shape and flavor of your taste.

APPLICATIONS

Designed and manufactured to the highest engineering standards with inherent reliability and longevity for use in tough, hostile environments.

ACCURACY

The Teltek designed precision engineered weigh platforms guarantees weight stability, accuracy and repeatability.

DESIGN

Available fabricated in stainless steel, IP65 with conveyors driven by virtually maintenance free, brushless DC motors.

REJECTS

Teltek C80 offers a range of belt sizes and reject devices to suit customer specific needs including air blast, pusher, single or double flipper/divert arm and drop flap.

COMMUNICATION CAPABILITIES

The Teltek C80 is feature packed with wide ranging Networking, Feedback and Communications capabilities, giving management and operators total control over their production line monitoring. Up to four parallel weighing systems can be controlled by one HMI.

REPORTS

Teltek C80 can produce production reports in Microsoft Excel™, PDF™ and or CSV. The reports can be saved locally, downloaded to the USB port or transferred across the customer network.

MID & CE CERTIFIED

The Teltek C80 is approved in accordance with European MID standards – assuring you obtain accurate measurement results at all times.

C80 Checkweigher



SPECIFICATIONS:

Weight capacity:	15-60 000 grams
Accuracy:	from 0,1 grams
Speed:	up to 500 ppm (depending on pack size)
Weigh platform:	Teltek C
Display/Control panel:	15" LED touch screen
Available Funtionality:	Reject confirmation, Bin full sensors, Remote access Air pressure monitor, Piece counting, Filling control, Sorting of weight zones, Safely Interlocks, Operator traceability
Available Languages:	English, Danish, Turkish, Hungarian, Spanish, Finnish, French, Serbia, Netherlands, Russian, Romanian, Czech, German and Swedish
Environmental Conditions:	Operating temperature +5°C to +40°C Humidity 20-90% non-condensing
Power:	110/230 VAC 50/60Hz
Dimensions:	All checkweighers built to customer specifications (belt dimensions)
Conveying:	Conveying direction right to left or left to right
Combination System:	Metal Detector, Xray Inspection, Vision Inspection & Label applicator
Software:	InControl is available to connect a network of Teltek Checkweigher in order to produce real time reporting across all production lines